

BP250.XX.1000 POLYURETHANE MATT PAINT WHITE

BP250.XX.1000 is two component polyurethane based matt white topcoat paint. BP250.XX.1000 polyurethane topcoat white is developed and presented to the market due to increasing customer demands which are high hiding power and best levelling regarding price/performance balance.

The product differs from the other white paints with the following properties below;

PRODUCT PROPERTIES

- Fast drying
- Good levelling
- Good touch
- High scratch resistance
- High hiding power

The product can be used for all kind of interior wooden surfaces in furniture industry, especially designed for kitchens, bathrooms and doors. The product can be applied with airmix or conventional spray guns.

DRYING TIME (20 C° , % 45-65 RH, 100 g/m²)

DUST FREE	15 - 20 min.
TOUCH DRY	45 - 60 min.
STACKABLE	24 h



TECHNICAL SPECIFICATONS OF GENÇ POLYURETHANE MATT PAINT WHITE

PRODUCT	POLYURETHANE HARDENER	MIXING RATIO	NON VOLATILE MATTER I.COMP (%)	NON VOLATILE MATTER I + 2 COMP (%)	VISCOSITY (KU, 25°C)	DENSITY (g/cm ³)	POT LIFE (20°C, h)
BP250.XX.1000	HP250.00	100/50	71	64	98	1,38	Min 4
BP588.XX.1000	HP588.00	100/50	72	62,7	97	1,39	Min 5

BP250.XX.1000
POLYURETHANE MATT PAINT WHITE



COMPARISON TABLE FOR GENÇ POLYURETHANE MATT PAINT WHITE

	BP250.XX.1000	BP588.XX.1000
Automatic Spray Machine	✓	✓
Airmix Spray	✓	✓
Conventional Spray	✓	✓
Hiding Power	++	++
Whiteness	+++	+++
Yellowing Resistance	++	+++
Homogeneous Appearance	+++	++

+++ : Best
++ : Good
+ : Average