

**BK100.XX
SERTLAKE MATT SERIES PAINT**



FEATURES

- High adhesion
- High hiding power
- High yellowing resistance
- Long pot-life
- Resistance to physical and chemical agents

DRYING TIME (20 °C, 45-65% RH, 100 g/m²)


Dust Free	7 - 10 min
Touch Dry	20 - 30 min
Stackable	16 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Sertlake Matt Series Paint	BK100.XX	100	110
Sertlake Hardener	HK100	25	30
Cellulosic Thinner	TN200	40 - 50	50 - 60

GLOSS OPTIONS

- 10 Matt
- 30 Medium Matt
- 50 Silk Matt

APPLICATION METHOD



SURFACE PREPARATION

Before application, the surface must be removed from dust and other foreign materials (oil, silicone, etc.).

It can be applied directly to melamine surfaces. In single layer primer or barrier-free applications, it is recommended to do light rough sanding on the surface will increase the adhesion resistance of the paint.

PACKAGING

3 KG/12 KG

COLOR OPTIONS



1000
White

KEY INFO

It can be applied directly to melamine surfaces or used as a barrier.

The product to be used should be applied within 60 minutes in cases where it is used as a barrier.

It can be applied on steel, metal, aluminum, PVC, melamine and wood surfaces.

It is recommended to make a small application on the surface to be applied before, after the adhesion is checked, to start the main application.

