

BS100.77 SYNTHETIC PRIMER



FEATURES

- High hiding power
- Easy of application
- Excellent adhesion

DRYING TIME (20 °C, 45-65% RH, 150 g/m²)

Dust Free	15 - 20 min
Touch Dry	25 - 30 min
Sandability	20 - 24 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Synthetic Primer	BS100.77	100	110
Synthetic Thinner	TS100	5 - 10	5 - 10

APPLICATION METHOD



SURFACE PREPARATION

If it is applied to walls; rough surfaces should be smoothed with interior wall putty. On old painted surfaces, the surface should be smoothed with sandpaper and if necessary paste should be applied. If it is applied to wooden surfaces; on new wooden surfaces; knots should be burned, it is recommended to be saturated with one layer Genç BS500 Woodtex Transparent Wood Primer in order to protect the wood.

If it is applied to metal surfaces; before application to old metal surfaces; to remove old and swollen paint residues, the residues should be scraped and cleaned. If there is a rust layer; the surface should be removed from rust with sandpaper and Genç Synthetic Antirust should be applied as a primer. If it is apply to on new metal surfaces; after the surface is cleaned, Genç Synthetic Antirust is applied before the topcoat.

PACKAGING

2.5 LT

COLOR OPTIONS



1000
White

KEY INFO

It can be used on walls, wood and metal surfaces before synthetic topcoat application.

