

BS200.00
SYNTHETIC GLOSSY PAINT



FEATURES

- Excellent levelling
- Resistance to physical and chemical agents
- Glossy and flexible surface
- Easy of application
- Without leaving brushmark

DRYING TIME (20 °C, 45-65% RH, 100 g/m²)

Dust Free	3 - 4 h
Touch Dry	5 - 6 h
Sandability	24 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Synthetic Glossy Paint	BS200.00	100	105
Synthetic Thinner	TS100	10 - 15	10 - 15

GLOSS OPTIONS

- 00 Glossy

APPLICATION METHOD



SURFACE PREPARATION

If it is applied to wooden surfaces; before applying on old wooden surfaces, paint residues should be cleaned and the surface should be sanded. On new wooden surfaces; knots should be burned, it is recommended to be saturated with one layer Genç BS500 Woodtex Transparent Wood Primer for protection of wood. Genç Synthetic Primer should be applied before the topcoat.

In the applications to be made on metal surfaces; old and swollen paint residuals should be scraped and the surface should be remove from rust. Genç Synthetic Antirust should be applied as a primer before the topcoat application.

PACKAGING

0.75 LT/ 2.5 LT / 15 LT

COLOR OPTIONS



KEY INFO

It can be used to protect internal and external surfaces of wood and iron structural elements in metal constructions, doors, windows, railings, etc and to provide decorative appearance.

