

**BS200.10**  
**SYNTHETIC MATT PAINT**



**FEATURES**

- Excellent levelling
- Resistance to physical and chemical agents
- Easy of application

**DRYING TIME (20 °C, 45-65% RH, 100 g/m<sup>2</sup>)**

Dust Free	3 - 4 h
Touch Dry	4 - 6 h
Stackable	48 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Synthetic Matt Paint	BS200.10	100	110
Synthetic Thinner	TS100	10 - 15	10 - 15

**GLOSS OPTIONS**

- 10 Matt

**APPLICATION METHOD**



**SURFACE PREPARATION**

If it is applied to wooden surfaces; before applying on old wooden surfaces, paint residues should be cleaned and the surface should be sanded. On new wooden surfaces; knots should be burned, it is recommended to be saturated with one layer Genç BS500 Woodtex Transparent Wood Primer for protection of wood. Genç Synthetic Primer should be applied before the topcoat.

In the applications to be made on metal surfaces; old and swollen paint residuals should be scraped and the surface should be remove from rust. Genç Synthetic Antirust should be applied as a primer before the topcoat application.

**PACKAGING**

0.75 LT / 2.5 LT / 15 LT

**COLOR OPTIONS**



1000  
White



9103  
Black

**KEY INFO**

It can be used to protect internal and external surfaces of wood and iron structural elements in metal constructions, doors, windows, railings, etc and to provide decorative appearance.

