

**VP526.00
POLYURETHANE GLOSSY VARNISH**



FEATURES

- Fast drying
- High flow resistance (can be applied on vertical surfaces)
- High and permanent gloss
- Scratch and impact resistance
- Polished after 24 hours

KEY INFO
It is especially recommended for vertical applications which has very fast drying and high glossy features.


DRYING TIME (20 °C, 45-65% RH, 100 g/m ²)	
Dust Free	20 - 30 min
Touch Dry	60 - 70 min
Stackable (500 kg/m ²)	16 - 18 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Polyurethane Glossy Varnish	VP526.00	100	100
Polyurethane Hardener	HP126	100	102
Polyurethane Thinner	TP100	0 - 10	0 - 10

GLOSS OPTIONS

- 00 Glossy

APPLICATION METHOD



SURFACE PREPARATION

The best performance is achieved to be applied on previously sanded surfaces which are pre-coated with GENÇ polyurethane, polyester or UV sanding sealer. Surface must be clean and dust free; remove all dirt (dust, wax etc.). If the topcoat is desired to be colored, ZD900 Gençmix Varnish Colorant can be used as the defined in the technical data sheet. PM901 Pearl Paste can be used to obtain required effect as shining. It is recommended to apply only glossy varnish on the first coat and the next coat with pearlescent or 2 or more coat applications.

PACKAGING

3 KG / 12 KG

