

**VP509.XX**  
**POLYURETHANE MATT SERIES VARNISH**



**FEATURES**

- Homogeneous matt appearance
- Easy application
- Fast drying
- High scratch resistance

**DRYING TIME (20 °C, 45-65% RH, 100 g/m<sup>2</sup>)**


Dust Free	10 - 15 min
Touch Dry	20 - 25 min
Stackable (500 kg/m <sup>2</sup> )	8 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Polyurethane Matt Series Varnish	VP509.XX	100	100
Polyurethane Hardener	HP600	50	53
Polyurethane Thinner	TP100	50	55

**GLOSS OPTIONS**

- 10 Matt
- 20 Special Matt
- 30 Medium Matt
- 40 Silk Matt
- 50 Silk Matt
- 60 Semi - Matt

**APPLICATION METHOD**



**SURFACE PREPARATION**

The best performance is achieved to be applied on previously sanded surfaces which are pre-coated with GENÇ polyurethane, polyester or UV sanding sealer. Surface must be clean and dust free; remove all dirt (dust, wax etc.). If the topcoat is desired to be colored, ZD900 Gençmix Varnish Colorant can be used as the defined in the technical data sheet. PM901 Pearl Paste can be used to obtain required effect as shining.

**PACKAGING**

3 KG / 12 KG

**KEY INFO**

It is a varnish that can be used on an artificial coatings. It is suitable for manufacturers projects of office furniture, chairs, tables and doors.

