

VA700.XX UV RESISTANT ACRYLIC MATT SERIES VARNISH



FEATURES

- High resistant to UV rays
- Excellent silky touch effect
- Excellent transparency
- Suitable for bleached wood
- Protect white and pastel colored surfaces against yellowing

DRYING TIME (20 °C, 45-65% RH, 100 g/m²)

Dust Free	10-15 min
Touch Dry	45-60 min
Stackable	min 16 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Acrylic Matt Series Varnish	VA700.XX	100	100
Acrylic Hardener	HA190	10	10
Acrylic Thinner	TA500	20 - 50	20 -55

GLOSS OPTIONS

- 05 Full Matt
- 10 Matt

APPLICATION METHOD



SURFACE PREPARATION

Surfaces to be applied; removed from dust, and other foreign materials (oil, silicone, varnish residues, etc.).

VA700.77 UV Resistant Acrylic Sealer should be used in nonyellowing varnish systems.

PACKAGING

15 KG

KEY INFO

It provides resistance to harmful rays coming from the sun and ensures minimum color change on the floor. It can prevent color change that may occur over time in colored coatings.

It is formulated for interior wooden furniture of sea transport vehicles. 05 Full Matt gloss option has excellent silky touch effect and the ability to hide application errors.

