

VA500.XX
ACRYLIC MAT SERIES VARNISH



FEATURES

- Excellent yellowing resistance
- Fast drying
- Silky touch effect


DRYING TIME (20° C, 45-65% RH, 100 g/m ²)	
Dust Free	10 - 15 min
Touch Dry	20 - 25 min
Stackable (500 kg/m ²)	16 - 17 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Acrylic Matt Series Varnish	VA500.XX	100	100
Acrylic Hardener	HA190	10	10
Acrylic Thinner	TA550	40	45

GLOSS OPTIONS

- 05 Full Matt
- 10 Matt
- 25 Special Matt
- 40 Silk Matt

APPLICATION METHOD



SURFACE PREPARATION

Before application, the surface must be removed from dust and other foreign materials (oil, silicone, varnish residues, etc.). For high yellowing resistance, acrylic systems can be used as basecoat. It can be applied as an intermediate coat and top coat by adding PM901 metallic and pearl paste.

PACKAGING

3 KG / 15 KG

KEY INFO
It can be apply on wood, also pre-tested metal surfaces. It is designed for high quality closed pore applications. It doesn't cause pinhole problems in oven even if applied in high quantity.

