

VA520 ACRYLIC VARNISH GLOSSY

VA520 is a two component, acrylic based, high gloss topcoat varnish. VA520 Acrylic Varnish Glossy is developed and presented to the market due to increasing customer demands which are high yellowing resistance and high glossy regarding price/performance balance. The product differs from the other topcoat varnishes with the following properties below;

PRODUCT PROPERTIES

- High yellowing resistance
- High glossy
- Excellent transparency
- Excellent levelling

It is used furniture industry can be applied to all types of interior wood surfaces. They are particularly suitable for light colored timber (maple, birch, ash, etc.) applications. Use on exterior surfaces is not recommended. The product can be applied with airmix or conventional spray guns.

DRYING TIME (20 C° , 45-65% RH, 100 g/m ²)	
DUST FREE	20 - 25 min.
TOUCH DRY	3 h.
STACKABLE (500 kg/m ²)	min. 24 h.
STACKABLE (1000 kg/m ²)	min. 30 h.



TECHNICAL SPECIFICATIONS OF GENÇ ACRYLIC VARNISH GLOSSY							
PRODUCT	ACRYLIC HARDENER	MIXING RATIO	NON VOLATILE MATTER I.COMP (%)	NON VOLATILE MATTER I + 2 COMP (%)	VISCOSITY (KU, 25°C)	DENSITY (g/cm ³)	POT LIFE (20°C, h.)
VA520	HA520.00	100/50	42 ± 2	40 ± 2	35 - 45"	1,00 ± 0,03	4
VA510	HA190.00	100/50	47 ± 2	43 ± 2	40 - 50"	0,985 ± 0,03	4

VA520 ACRYLIC VARNISH GLOSSY



COMPARISON TABLE FOR GENÇ ACRYLIC VARNISH GLOSSY

	VA520	VA510
Automatic Spray Machine	✓	✓
Airmix Spray	✓	✓
Conventional Spray	✓	✓
Yellowing Resistance	+++	+++
Glossy	+++	+
Transparency	++	++
Levelling	++	++
Drying	+++	+

+++ : Best
++ : Good
+ : Average