

VA300.XX.0000 ACRYLIC VARNISH MATT SERIES

VA300.XX.0000 acrylic based, two component matt series varnish.

VA300.XX.0000 Acrylic Varnish Matt Series is developed and presented to the market due to increasing customer demands which high performance in open pore applications regarding price/performance balance. The product differs from the other varnishes with the following properties below;

PRODUCT PROPERTIES

- High performance in open pore applications
- Fast drying
- Transparent homogeneous matt distribution
- Soft touch and flexible film

It is used for furniture and decoration works for interior use, to provide protection and decorative appearance on all kinds of wooden surfaces such as massive and veneer (especially on light colored woods, white and pastel painted surfaces). The product can be applied with airmix, airless or conventional spray guns.

DRYING TIME (20 C°, % 45-65 RH, 100 g/m²)	
DUST FREE	25 - 30 min.
TOUCH DRY	40 - 50 min.
STACKABLE (500 kg/m²)	2 - 3 h.
STACKABLE (1000 kg/m²)	7 - 8 h.



TECHNICAL SPECIFICATIONS OF GENÇ ACRYLIC VARNISH MATT SERIES

PRODUCT	ACRYLIC HARDENER	MIXING RATIO	NON VOLATILE MATTER I.COMP (%)	NON VOLATILE MATTER I + 2 COMP (%)	VISCOSITY (KU, 25°C)	DENSITY (g/cm³)	POT LIFE (20°C, h)
VA300.XX.0000	HA300.00	100/10	22 ± 2	22,5 ± 2	40 - 65	0,94 ± 0,03	7
VA503.XX.0000	HA190.00	100/10	23 ± 2	24 ± 2	35 - 50	0,92 ± 0,03	Min. 8

VA300.XX.0000
ACRYLIC VARNISH MATT SERIES



COMPARISON TABLE FOR GENÇ ACRYLIC VARNISH MATT SERIES

	VA300.XX.0000	VA503.XX.0000
Automatic Spray Machine	✓	✓
Airmix Spray	✓	✓
Conventional Spray	✓	✓
Open Pore Applications	+++	++
Homogeneous Appearance	+++	+++
Fast Drying	++	+

+++ : Best
++ : Good
+ : Average