

BP440 POLYURETHANE SELF PRIMER PAINT

BP440 is two component polyurethane based white self primer matt paint. BP440 Polyurethane Self Primer Paint has been produced and presented to the market provide for maximum resistance to cracking, excellent adhesion and high flexibility product need. The product differs from the other polyurethanes with the following properties below.

PRODUCT PROPERTIES

- Maximum resistance to cracking
- Excellent adhesion
- High flexibility
- High filling capacity and hiding power
- Fast drying
- Excellent levelling
- Soft touch
- Easy sanding
- High amount applicability

It can be used for furniture and decoration works to provide protection and decorative appearance on all types of wooden surfaces such as massive and MDF. Especially recommended for use in bathrooms, kitchen cabinets, doors, other furnitures. It's not recommended for parquets.



DRYING TIME (20°C, 45-65% RH, 100 g/m ²)	
DUST FREE	15 - 20 min.
TOUCH DRY	30 - 35 min.
STACKABLE (500 kg/m ²)	24 h.

TECHNICAL SPECIFICATONS OF GENÇ POLYURETHANE SELF PRIMER PAINT							
PRODUCT	POLYURETHANE HARDENER	MIXING RATIO	NON VOLATILE MATTER I.COMP (%)	NON VOLATILE MATTER I + 2 COMP (%)	VISCOSITY (KU, 25°C)	DENSITY (g/cm ³)	POT LIFE (20°C, h.)
BP440	HP440	100/50	74 ± 2	57 ± 2	100 - 105	1,43 ± 0,03	4 - 5

BP440
POLYURETHANE SELF PRIMER PAINT



FEATURES TABLE FOR GENÇ POLYURETHANE SELF PRIMER PAINT

	BP440
Automatic Spray Machine	✓
Airmix Spray	✓
Conventional Spray	✓
Resistance to Cracking	+++
Adhesion	+++
Flexibility	+++
Filling Capacity and Hiding Power	+++
Whiteness	+++
Levelling	+++

+++ Best
++ Good
+ Average