CELLULOSIC PRODUCT GROUP



BN100.00 CELLULOSIC GLOSSY PAINT

FEATURES

- High hiding power
- High glossy
- Trend colors
- Excellent levelling

DRYING TIME (20°C, 45-65% RH, 100 g/m ²)		
Dust Free	10 - 15 min	
Touch Dry	30 - 40 min	

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Cellulosic Glossy Paint	BN100.00	100	110
Cellulosic Thinner	TN200	80 - 100	100 - 120

GLOSS OPTIONS

• 00 Glossy

APPLICATION METHOD



SURFACE PREPARATION

To be applied on Genç Polyurethane, Polyester or UV basecoat which are preferably sanded with no 220-280-400 or 280-400 grit sandpaper respectively. The sanding process to be performed as indicated is enough before the topcoat application. If extra sanding is to be carried out, the sanding size of 600 grit should not be exceeded. If exceeded, the adhesion properties should be checked.

PACKAGING

0.75 LT / 2.5 LT / 12 KG

KEY INFO

Due to its fast drying, it can be easily preferred for wood and metal surfaces in furniture and decoration works. It enables a combination of vivid and trendy colors in your furniture.







