

## BN100.10 CELLULOSIC MATT PAINT

### FEATURES

- Homogeneous matt appearance
- High hiding power
- Excellent levelling
- Fast drying

#### DRYING TIME (20 °C, 45-65% RH, 100 g/m<sup>2</sup>)

|                                    |             |
|------------------------------------|-------------|
| Dust Free                          | 7 min       |
| Touch Dry                          | 10 - 12 min |
| Stackable (500 kg/m <sup>2</sup> ) | 60 min      |

| PRODUCT               | CODE     | BY WEIGHT (%) | BY VOLUME (%) |
|-----------------------|----------|---------------|---------------|
| Cellulosic Matt Paint | BN100.10 | 100           | 110           |
| Cellulosic Thinner    | TN200    | 80 - 100      | 100 - 120     |

### GLOSS OPTIONS

- 10 Matt

### APPLICATION METHOD




### SURFACE PREPARATION

To be applied on Genç Polyurethane, Polyester or UV Basecoat which are preferably sanded with 220-280-400 or 280-400 grit sandpaper respectively. The sanding process to be performed as indicated is enough before the topcoat application. If extra sanding is to be carried out, the sanding size of 600 grit should not be exceeded. If exceeded, the adhesion properties should be checked.

### PACKAGING

0.75 LT / 2.5 LT/ 12 KG

### COLOR OPTIONS



1110  
White



9103  
Black

### KEY INFO

Due to its fast drying, it can be easily preferred for wood and metal surfaces in furniture and decoration works.

