

## CP585.00

### POLYURETHANE CONVERTER GLOSSY PAINT (TINTING)



#### FEATURES

- High yellowing resistance
- Homogeneous surface
- High hiding power
- Fast drying

#### DRYING TIME (20 °C, 45-65% RH, 100 g/m<sup>2</sup>)

Dust Free	20 - 25 min
Touch Dry	45 - 60 min
Stackable (500 kg/m <sup>2</sup> )	24 - 30 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Polyurethane Converter Glossy Paint	CP585.00	100	110
Polyurethane Hardener	HP580	50	60
Acrylic Thinner	TA500	20	30

#### KEY INFO

In polyurethane systems, Genç Tinting Technology is used for the preparation of RAL, NCS, Pantone and other colors.


It is suitable for kitchen, bathroom cabinets and lacquer furnitures.

Genç HP120 Polyurethane Hardener can be used as alternative hardener.

#### GLOSS OPTIONS

- 00 Parlak

#### APPLICATION METHOD



#### SURFACE PREPARATION

To be applied on Genç Polyurethane, Polyester or UV Basecoat which are preferably sanded with 240-400 grit sandpaper.

After sanding, surface must be clean and dust free; removed from all contamination (oil, silicone etc.) before the topcoat application.

#### PACKAGING

- 3 KG / 12 KG WHITE
- 2.7 KG / 10.8 KG SEMI - WHITE
- 2.4 KG / 9.6 KG TRANSPARENT

#### COLOR OPTIONS



Any color can be made with the Genç Tinting system.

