

**VS100.XX  
SYNTHETIC PARQUET VARNISH**



**FEATURES**

- Resistance to physical and chemical agents
- Smooth surface
- High scratch resistance
- Easily cleaned by soap or detergent

DRYING TIME (20 °C, 45-65% RH, 100 g/m <sup>2</sup> )	
Dust Free	1 - 2 h
Touch Dry	2 - 4 h
Full Drying	24 - 48 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Synthetic Parquet Varnish	VS100.XX	100	100
Synthetic Thinner	TS100	10 - 20	12 - 25

**KEY INFO**

After thinning with synthetic thinner, it is recommended to wait at least 20 min. for removal of foaming during mixing.

It reaches physical and chemical resistance on maximum fourth day.

**GLOSS OPTIONS**

- 00 Glossy
- 10 Matt
- 20 Special Matt
- 40 Silk Matt

**APPLICATION METHOD**



**SURFACE PREPARATION**

It can be applied to surfaces that have been applied with polyurethane or cellulosic sealer, preferably sanded with 220-240-400 grit sandpaper respectively. After sanding, the surface must be removed from dust and other foreign materials (oil, silicone, etc.)

**PACKAGING**

0.75 LT/ 2.5 LT / 12 KG

