

VP850.77
POLYURETHANE SEALER



FEATURES

- High transparency
- Easy sanding
- High filling power

DRYING TIME (20 °C, 45-65% RH, 100 g/m²)


Dust Free	10 - 15 min
Touch Dry	15 - 20 min
Sandability	45 - 60 min

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Polyurethane Sealer	VP850.77	100	100
Polyurethane Hardener	HP777	50	53
Polyurethane Thinner	TP100	30 - 40	35 - 45

KEY INFO

It is a high transparent sealer which is developed to create high body surface before topcoat application. It is recommended to use with HP900 PU Hardener at over 25 °C and 55% humidity. It is recommended to wait 24 hours before glossy varnish topcoat applications.

APPLICATION METHOD



SURFACE PREPARATION

Before application, the surface must be sanded with 180-220 sandpaper, remove dust and other foreign materials (oil, silicone, varnish residues, etc.). If the surface is desired to be colored, it can be stained using ZD820 Gençcolor Wood Stain or BS600 Woodtex Wood Colourant. For coloring the varnish, ZD900 Gençmix Varnish Colorant can be used as the defined in the technical data sheet.

PACKAGING

3 KG / 12 KG

