

## VP350.77 POLYURETHANE SEALER



### FEATURES

- Fast drying
- Easy sanding
- High filling power

#### DRYING TIME (20 °C, 45-65% RH, 100 g/m<sup>2</sup>)

Dust Free	15 - 20 min
Touch Dry	40 - 45 min
Sandability	60 - 90 min

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Polyurethane Sealer	VP350.77	100	100
Polyurethane Hardener	HP777	50	53
Polyurethane Thinner	TP100	30	35

### KEY INFO

It is general use purpose sealer which is designed for applications where fast and easy sanding are required. It is suitable for light colored wooden surfaces. It is not recommended to be used on dark colored wooden surfaces more than 120 g/m<sup>2</sup>.

### APPLICATION METHOD



### SURFACE PREPARATION

Before application, the surface must be sanded with 180-220 sandpaper, remove dust and other foreign materials (oil, silicone, varnish residues, etc). If the surface is desired to be colored, it can be stained using ZD820 Gençcolor Wood Stain or BS600 Woodtex Wood Colourant. For coloring the varnish, ZD900 Gençmix Varnish Colorant can be used as the defined in the technical data sheet.

### PACKAGING

3 KG / 12 KG

