

**BP100.00
POLYURETHANE GLOSSY PAINT**



FEATURES

- High body
- High and permanent glossy
- Very good levelling


| DRYING TIME (20 °C, 45-65% RH, 100 g/m ²) | |
|---|-------------|
| Dust Free | 10 - 15 min |
| Touch Dry | 50 - 60 min |
| Stackable (500 kg/m ²) | 23 - 25 h |

| PRODUCT | CODE | BY WEIGHT (%) | BY VOLUME (%) |
|---------------------------|----------|---------------|---------------|
| Polyurethane Glossy Paint | BP100.00 | 100 | 110 - 120 |
| Polyurethane Hardener | HP900 | 50 | 55 |
| Polyurethane Thinner | TP100 | 20 | 25 |

GLOSS OPTIONS

- 00 Glossy

APPLICATION METHOD



SURFACE PREPARATION

To be applied on Genç Polyurethane, Polyester or UV Basecoat which are preferably sanded with 220-280-400 or 220-400 grit sandpaper respectively.

PACKAGING

3 KG / 12 KG

COLOR OPTIONS



1000
White

9103
Black

KEY INFO

It can be used with HP501 hardener in case of yellowing resistance.

It can be colored up to 5% (by weight) with Genç Cellulosic colored paints.

