

**BP545.XX
POLYURETHANE MATT SERIES PAINT**



FEATURES

- Excellent homogeneous matt and appearance
- Excellent levelling
- Fast drying
- Vertical and horizontal applicability

DRYING TIME (20 °C, 45 - 65% RH, 100 g/m²)


Dust Free	10 - 15 min
Touch Dry	30 - 40 min
Stackable	min. 16 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Polyurethane Matt Series Paint	BP545.XX	100	110 - 120
Polyurethane Hardener	HP545	50	55
Polyurethane Thinner	TP100	35 - 40	40 - 50

GLOSS OPTIONS

- 05 Full Matt
- 10 Matt

APPLICATION METHOD



SURFACE PREPARATION

To be applied on Genç Polyurethane, Polyester or UV basecoat which are preferably sanded with 220-280-400 or 220-400 grit sandpaper respectively.

PACKAGING

12 KG

COLOR OPTIONS



1000
White

*It is suitable for coloring.

KEY INFO

It can be easily applied and excellent surface appearance obtained even if there is no professional application conditions.

There is no defect on the surface when foreign particals (dust etc.), caused by ambiance, picked up from the surface in a short time on wet film which is applied over 180 g/m²

