

## BP702.50 POLYURETHANE PANEL DOOR PAINT


### FEATURES

- Flow resistance
- Good hiding power
- Fast drying

DRYING TIME (20 °C, 45-65% RH, 100 g/m <sup>2</sup> )	
Dust Free	30 min
Touch Dry	1 - 2 h
Stackable (500 kg/m <sup>2</sup> )	36 h

PRODUCT	CODE	BY WEIGHT (%)	BY VOLUME (%)
Polyurethane Panel Door Paint	BP702.50	100	110 - 120
Polyurethane Hardener	HP900	25	30
Polyurethane Thinner	TP100	25 - 30	30-35

### APPLICATION METHOD



### SURFACE PREPARATION

It is recommended to apply on door skinned surfaces and Genç polyurethane primered panel doors on sanded surface which are preferably sanded with 220, 400 grit sandpaper.

### GLOSS OPTIONS

- 50 Silky Mat

### PACKAGING

20 KG

### COLOR OPTIONS



1001  
Snow  
White

1013  
Pearl  
White

1511  
Off-White

**KEY INFO**  
It is compatible with polyurethane and cellulosic color pastes.  
It can be applied up to 200-220 gr/m<sup>2</sup> for one coat.  
It is specially designed to achieve high quality results without primer in white colored applications.

