

VA107 ACRYLIC SEALER

VA107 is acrylic based, two component sealer.

VA107 Acrylic Sealer has been produced and presented to the market provide for high yellowing resistance product need. The product differs from the other sealers with the following properties below.

PRODUCT PROPERTIES

- High yellowing resistance
- Suitable for bleached and light colored woods
- Easy sanding
- Suitable for open/close pore application

It can be used for furniture and decoration works for internal use especially to provide protection and decorative appearance on light colored woods (maple, birch, ash, oak) and white, pastel colored surfaces. The product can be applied with airmix, airless or conventional spray guns.



DRYING TIME (20 C °, 45-65 % RH, 150 g/m²)

DUST FREE	10 - 15 min.
TOUCH DRY	15 - 20 min.
SANDABILITY	80 - 100 min.

TECHNICAL SPECIFICATONS OF GENÇ ACRYLIC SEALER

PRODUCT	ACRYLIC HARDENER	MIXING RATIO	NON VOLATILE MATTER I.COMP (%)	NON VOLATILE MATTER 1 + 2 COMP (%)	VISCOSITY (KU, 25°C)	DENSITY (g/cm ³)	POT LIFE (20°C, h)
VA107	HA197	100/10	26 ± 2	26 ± 2	45 - 55	0,94 ± 0,03	7
VA104	HA190	100/10	25 ± 2	26 ± 2	45 - 55	0,93 ± 0,03	7

* Product can be applied 1-2 coats (100-150 gr/m², for one coat) . According to the weather conditions, should be waiting minimum 1 hour, maximum 4 hours between coats.

VA107 ACRYLIC SEALER



COMPARISON TABLE FOR GENÇ ACRYLIC SEALER

	VA107	VA104
Automatic Spray Machine	✓	✓
Airmix Spray	✓	✓
Conventional Spray	✓	✓
Yellowing Resistance	+++	+++
Filling Capacity	++	++
Open/Close Pore Application	++	+++
Sandability	+	+++

+++ : Best
++ : Good
+ : Average